

On receiving ReorderNetwork with:

- NetworkID = FancyCat
- NetworkIndex = 3

The outcome, after applying to the **initial state** would be:

Index in list	NetworkID field	Connected field
0	BlueDolphin	true
1	Home-Guest	false
2	WillowTree	false
3	FancyCat	false

In the above outcome, BlueDolphin, Home-Guest and WillowTree moved "up" and FancyCat became the lowest priority network in the list.

11.9.8. Usage of networking configurations

This section describes how to ensure deterministic and well-behaved network connectivity, both when concurrent and non-concurrent commissioning flows (see [Section 5.5, "Commissioning Flows"](#)) are used.

Operational Networking configuration is managed by the set of Network Commissioning cluster server instances distributed on a Node's Endpoints.

Since Matter employs IPv6 communication and DNS-SD for operational [Discovery](#), there is a fundamental aspect of multi-homing present, where a Node with multiple concurrently operated network interfaces device may be reachable using a variety of addresses on different network technologies. Care **SHOULD** be taken by Administrators and Commissioners to avoid making strong assumptions about single address reachability. Administrators and Commissioners **SHOULD** be prepared to attempt reachability tests against specific network technologies if the final desired state of networking requires a specific reachable path.

A Node **MAY** be configured in such a way that there are no Network Commissioning cluster server instances present, in which case the remainder of this section **SHALL NOT** apply.

11.9.8.1. Network Interfaces

Primary Network Interface

The primary network interface of a Node **SHALL** be the one present on the root node endpoint (see [Section 9.2, "Endpoint Composition"](#)). This interface is expected to be the one most likely to yield an operational reachable state if appropriately configured.

Secondary Network Interfaces

The secondary network interfaces **SHOULD** be additional technologies that **MAY** increase reachability or support a [stub router feature](#). These interfaces **SHALL** be hosted by endpoints other than the