

FailSafeExpiryLengthSeconds Field

This field SHALL contain a conservative initial duration (in seconds) to set in the FailSafe for the commissioning flow to complete successfully. This may vary depending on the speed or sleepiness of the Commissionee. This value, if used in the [Section 11.10.7.2, “ArmFailSafe”](#) command’s ExpiryLengthSeconds field SHOULD allow a Commissioner to proceed with a nominal commissioning without having to-rearm the fail-safe, with some margin.

MaxCumulativeFailsafeSeconds Field

This field SHALL contain a conservative value in seconds denoting the maximum total duration for which a fail safe timer can be re-armed. See [Section 11.10.7.2.1, “Fail Safe Context”](#).

The value of this field SHALL be greater than or equal to the FailSafeExpiryLengthSeconds. Absent additional guidelines, it is RECOMMENDED that the value of this field be aligned with the initial [Section 5.4.2.3, “Announcement Duration”](#) and default to 900 seconds.

11.10.6. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	Bread-crumbs	uint64	all		0	RW VA	M
0x0001	BasicCommissioningInfo	BasicCommissioningInfo	desc	F		R V	M
0x0002	RegulatoryConfig	RegulatoryLocationTypeEnum	all		Location-Capability	R V	M
0x0003	Location-Capability	RegulatoryLocationTypeEnum	all	F	IndoorOutdoor	R V	M
0x0004	SupportsConcurrentConnection	bool	all	F	true	R V	M
0x0005	TCAcceptedVersion	uint16	all	N		R A	TC
0x0006	TCMinRequiredVersion	uint16	all	N		R A	TC