

11.10.6.8. TCAcknowledgements Attribute

This attribute SHALL indicate the user's response to the presented terms. Each bit position corresponds to a user response for the associated index of matching text, such that bit 0 (bit value 1) is for text index 0. Bit 15 (bit value 0x8000) is for text index 15. A bit value of 1 indicates acceptance and a value of 0 indicates non-acceptance. For example, if there are two texts that were presented where the first (bit 0, value 1) was declined and the second accepted (bit 1, value 2), we would expect the resulting value of the map to be 2.

Whenever a user provides responses to newly presented terms and conditions, this attribute SHALL be updated with the latest responses. This MAY happen in response to updated terms that were presented to the user. On a factory reset this field SHALL be reset with all bits set to 0.

11.10.6.9. TCAcknowledgementsRequired Attribute

This attribute SHALL indicate whether [SetTCAcknowledgements](#) is currently required to be called with the inclusion of mandatory terms accepted.

This attribute MAY be present and False in the case where no terms and conditions are currently mandatory to accept for [CommissioningComplete](#) command to succeed.

This attribute MAY appear, or become True after commissioning (e.g. due to a firmware update) to indicate that new Terms & Conditions are available that the user must accept.

Upon Factory Data Reset, this attribute SHALL be set to a value of True.

When [Section 5.7.3, "Custom Commissioning Flow"](#) is used to obtain user consent (e.g. because the Commissioner does not support the TC feature), the manufacturer-provided means for obtaining user consent SHALL ensure that this attribute is set to False before returning the user back to the original Commissioner (see [Section 5.7.4, "Enhanced Setup Flow \(ESF\)"](#)).

11.10.6.10. TCUpdateDeadline Attribute

This attribute SHALL indicate the System Time in seconds when any functionality limitations will begin due to a lack of acceptance of updated Terms and Conditions, as described in [Section 5.7.4.6, "Presenting Updated Terms and Conditions"](#).

A null value indicates that there is no pending deadline for updated TC acceptance.

11.10.6.11. RecoveryIdentifier Attribute

This attribute SHALL contain the identifier to be included in the advertisements used during the [Network Recovery Flow](#). This identifier is intended to be advertised over the air and used by an Administrator to establish a Node's identity without revealing its Node ID.

The attribute SHALL contain a random 64-bit value, that value SHALL be reset on factory reset and SHALL remain unchanged until a next factory reset. It is important that this value be selected at random from a 64-bit number space to ensure a high likelihood of uniqueness from values selected by other Nodes. This value SHOULD be obtained through `Crypto_DRBG(len = 64)`.