

**BDX Value**

SHALL be used by a Client to request that logs are transferred using BDX as defined in [BDX Protocol](#)

**11.11.5. Commands**

| ID   | Name                        | Direction       | Response             | Access | Conformance |
|------|-----------------------------|-----------------|----------------------|--------|-------------|
| 0x00 | <b>RetrieveLogsRequest</b>  | client ⇒ server | RetrieveLogsResponse | O      | M           |
| 0x01 | <b>RetrieveLogsResponse</b> | client ⇐ server | N                    |        | M           |

**11.11.5.1. RetrieveLogsRequest Command**

Reception of this command starts the process of retrieving diagnostic logs from a Node.

The data for this command is as follows:

| ID | Name                          | Type                                 | Constraint | Quality | Fallback | Conformance |
|----|-------------------------------|--------------------------------------|------------|---------|----------|-------------|
| 0  | <b>Intent</b>                 | <a href="#">IntentEnum</a>           | all        |         |          | M           |
| 1  | <b>RequestedProtocol</b>      | <a href="#">TransferProtocolEnum</a> | all        |         |          | M           |
| 2  | <b>TransferFileDesignator</b> | <a href="#">string</a>               | max 32     |         |          | O           |

**Intent Field**

This field SHALL indicate why the diagnostic logs are being retrieved from the Node. A Node MAY utilize this field to selectively determine the logs to transfer.

**RequestedProtocol Field**

This field SHALL be used to indicate how the log transfer is to be realized. If the field is set to BDX, then if the receiving Node supports BDX it SHALL attempt to use BDX to transfer any potential diagnostic logs; if the receiving Node does not support BDX then the Node SHALL follow the requirements defined for a TransferProtocolEnum of ResponsePayload. If this field is set to ResponsePayload the receiving Node SHALL only utilize the [LogContent](#) field of the RetrieveLogsResponse command to transfer diagnostic log information.

**TransferFileDesignator Field**

This field SHALL be present if the RequestedProtocol is BDX. The TransferFileDesignator SHALL be set as the [File Designator](#) of the BDX transfer if initiated.