

Effect on Receipt

On receipt of this command, the Node SHALL respond with a RetrieveLogsResponse command.

If the RequestedProtocol is set to BDX the Node SHOULD immediately realize the RetrieveLogsResponse command by initiating a [BDX Transfer](#), sending a [BDX SendInit](#) message with the File Designator field of the message set to the value of the TransferFileDesignator field of the RetrieveLogsRequest. On reception of a [BDX SendAccept](#) message the Node SHALL send a RetrieveLogsResponse command with a Status field set to Success and proceed with the log transfer over BDX. If a failure StatusReport is received in response to the SendInit message, the Node SHALL send a RetrieveLogsResponse command with a Status of Denied. In the case where the Node is able to fit the entirety of the requested logs within the [LogContent](#) field, the Status field of the RetrieveLogsResponse SHALL be set to Exhausted and a BDX session SHALL NOT be initiated.

If the RequestedProtocol is set to BDX and either the Node does not support BDX or it is not possible for the Node to establish a BDX session, then the Node SHALL utilize the [LogContent](#) field of the RetrieveLogsResponse command to transfer as much of the current logs as it can fit within the response, and the Status field of the RetrieveLogsResponse SHALL be set to Exhausted.

If the RequestedProtocol is set to ResponsePayload the Node SHALL utilize the [LogContent](#) field of the RetrieveLogsResponse command to transfer as much of the current logs as it can fit within the response, and a BDX session SHALL NOT be initiated.

If the RequestedProtocol is set to BDX and there is no TransferFileDesignator the command SHALL fail with a Status Code of INVALID_COMMAND.

If the Intent and/or the RequestedProtocol arguments contain invalid (out of range) values the command SHALL fail with a Status Code of INVALID_COMMAND.

11.11.5.2. RetrieveLogsResponse Command

This SHALL be generated as a response to the RetrieveLogsRequest.

The data for this command is shown in the following.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Status	StatusEnum	all			M
1	LogContent	octstr	max 1024			M
2	UTCTime-Stamp	epoch-us	all			O
3	TimeSince-Boot	systime-us	all			O

Status Field

This field SHALL indicate the result of an attempt to retrieve diagnostic logs.