

LogContent Field

This field SHALL be included in the command if the Status field has a value of Success or Exhausted. A Node SHOULD utilize this field to transfer the newest diagnostic log entries. This field SHALL be empty if BDX is requested and the Status field has a value of Success.

UTCTimeStamp Field

This field SHOULD be included in the command if the Status field has a value of Success and the Node maintains a wall clock. When included, the UTCTimeStamp field SHALL contain the value of the oldest log entry in the diagnostic logs that are being transferred.

TimeSinceBoot Field

This field SHOULD be included in the command if the Status field has a value of Success. When included, the TimeSinceBoot field SHALL contain the time of the oldest log entry in the diagnostic logs that are being transferred represented by the number of microseconds since the last time the Node went through a reboot.

11.12. General Diagnostics Cluster

The General Diagnostics Cluster, along with other diagnostics clusters, provide a means to acquire standardized diagnostics metrics that MAY be used by a Node to assist a user or Administrator in diagnosing potential problems. The General Diagnostics Cluster attempts to centralize all metrics that are broadly relevant to the majority of Nodes.

11.12.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision
2	UpTime attribute now mandatory, and added TimeSnapshot command, added DMTEST feature

11.12.2. Classification

Hierarchy	Role	Scope	PICS Code	Quality
Base	Utility	Node	DGGEN	K

11.12.3. Cluster ID

ID	Name
0x0033	General Diagnostics