

interface and contain the current extended MAC address for a 802.15.4 interface. The byte order of the [octstr](#) SHALL be in wire byte order. For addresses values less than 64 bits, the first two bytes SHALL be zero.

IPv4Addresses Field

This field SHALL provide a list of the IPv4 addresses that are currently assigned to the network interface.

IPv6Addresses Field

This field SHALL provide a list of the unicast IPv6 addresses that are currently assigned to the network interface. This list SHALL include the Node's link-local address and SHOULD include any assigned GUA and ULA addresses. This list SHALL NOT include any multicast group addresses to which the Node is subscribed.

Type Field

This field SHALL indicate the type of the interface using the [InterfaceTypeEnum](#).

11.12.6. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	Network-Interfaces	list[NetworkInterface]	max 8			R V	M
0x0001	Reboot-Count	uint16		N		R V	M
0x0002	UpTime	uint64		C		R V	M
0x0003	TotalOperational-Hours	uint32		C N		R V	O
0x0004	BootReason	BootReasonEnum				R V	O
0x0005	Active-Hardware-Faults	list[HardwareFaultEnum]	max 11			R V	O
0x0006	ActiveRadioFaults	list[RadioFaultEnum]	max 7			R V	O
0x0007	ActiveNetwork-Faults	list[NetworkFaultEnum]	max 4			R V	O