

field set to an empty octet string.

- If Value is 0xA5 and the Count is 10, the PayloadTestResponse would have the Payload field set to a content whose hexadecimal representation would be **A5A5A5A5A5A5A5A5A5**, and base64 representation would be **paWlpawlpawlpQ==**.

11.12.7.5. PayloadTestResponse Command

This command is sent by the server on receipt of the PayloadTestRequest command.

This command SHALL have the following data fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0x00	Payload	octstr	max 2048			M

Payload Field

This field SHALL contain the computed response of the PayloadTestRequest command.

11.12.8. Events

ID	Name	Priority	Quality	Access	Conformance
0x00	HardwareFaultChange	CRITICAL		V	O
0x01	RadioFaultChange	CRITICAL		V	O
0x02	NetworkFaultChange	CRITICAL		V	O
0x03	BootReason	CRITICAL		V	M

11.12.8.1. HardwareFaultChange Event

The HardwareFaultChange Event SHALL indicate a change in the set of hardware faults currently detected by the Node.

The data of this event SHALL contain the following information:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Current	list[HardwareFaultEnum]	max 11			M
1	Previous	list[HardwareFaultEnum]	max 11			M