

11.13.4. Features

This cluster SHALL support the FeatureMap bitmap attribute as defined below.

Bit	Code	Feature	Summary
0	WTRMRK	Watermarks	Node makes available the metrics for high watermark related to memory consumption.

11.13.5. Data Types

11.13.5.1. ThreadMetricsStruct Type

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	ID	uint64	all				M
1	Name	string	max 8		empty		O
2	Stack-FreeCurrent	uint32	all		MS		O
3	Stack-FreeMinimum	uint32	all		MS		O
4	StackSize	uint32	all		MS		O

ID Field

The Id field SHALL be a server-assigned per-thread unique ID that is constant for the duration of the thread. Efforts SHOULD be made to avoid reusing ID values when possible.

Name Field

The Name field SHALL be set to a vendor defined name or prefix of the software thread that is static for the duration of the thread.

StackFreeCurrent Field

The StackFreeCurrent field SHALL indicate the current amount of stack memory, in bytes, that are not being utilized on the respective thread.

StackFreeMinimum Field

The StackFreeMinimum field SHALL indicate the minimum amount of stack memory, in bytes, that has been available at any point between the current time and this attribute being reset or initialized on the respective thread. This value SHALL only be reset upon a Node reboot or upon receiving of the [ResetWatermarks](#) command.