

Name Field

This field SHALL be set to a manufacturer-specified name or prefix of the software thread in which the last software fault occurred.

FaultRecording Field

This field SHALL be a manufacturer-specified payload intended to convey information to assist in further diagnosing or debugging a software fault. The FaultRecording field MAY be used to convey information such as, but not limited to, thread backtraces or register contents.

11.14. Thread Network Diagnostics Cluster

The Thread Network Diagnostics Cluster provides a means to acquire standardized diagnostics metrics that MAY be used by a Node to assist a user or Administrator in diagnosing potential problems. The Thread Network Diagnostics Cluster attempts to centralize all metrics that are relevant to a potential Thread radio running on a Node.

11.14.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision
2	Remove optionality from FrameErrorRate and MessageErrorRate
3	Add ExtAddress and Rloc16 attributes

11.14.2. Classification

Hierarchy	Role	Scope	PICS Code	Quality
Base	Utility	Node	DGTHREAD	K

11.14.3. Cluster ID

ID	Name
0x0035	Thread Network Diagnostics

11.14.4. Features

This cluster SHALL support the FeatureMap bitmap attribute as defined below.