

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	ExtAddress	uint64					M
1	Rloc16	uint16					M
2	RouterId	uint8					M
3	NextHop	uint8					M
4	PathCost	uint8					M
5	LQIIn	uint8					M
6	LQIOut	uint8					M
7	Age	uint8					M
8	Allocated	bool					M
9	LinkEstablished	bool					M

ExtAddress Field

This field SHALL specify the IEEE 802.15.4 extended address for the Node for which this route table entry corresponds. The uint64 value is composed by taking the 8 octets of the extended address EUI-64 and treating them as a big-endian integer. For example, octet string (in hexadecimal, from first octet to last) **00112233AABBCCDD** would lead to a value of 0x00112233AABBCCDD.

Rloc16 Field

This field SHALL specify the RLOC16 for the Node for which this route table entry corresponds. The uint16 value is composed by taking the two RLOC16 and treating the octet string as if it was encoding a big-endian integer. For example, octet string (in hexadecimal, from first octet to last) **44AA** would lead to a value of 0x44AA.

RouterId Field

This field SHALL specify the Router ID for the Node for which this route table entry corresponds.

NextHop Field

This field SHALL specify the Router ID for the next hop in the route to the Node for which this route table entry corresponds.

PathCost Field

This Field SHALL specify the cost of the route to the Node for which this route table entry corresponds.

LQIIn Field

This field SHALL specify the implementation specific mix of IEEE 802.15.4 PDU receive quality indi-