

11.14.6.40. RxTotalCount Attribute

This attribute SHALL indicate the total number of received unique MAC frames. This value SHALL only be reset upon a Node reboot.

11.14.6.41. RxUnicastCount Attribute

This attribute SHALL indicate the total number of received unique unicast MAC frames. This value SHALL only be reset upon a Node reboot.

11.14.6.42. RxBroadcastCount Attribute

This attribute SHALL indicate the total number of received unique broadcast MAC frames. This value SHALL only be reset upon a Node reboot.

11.14.6.43. RxDataCount Attribute

This attribute SHALL indicate the total number of received unique MAC Data frames. This value SHALL only be reset upon a Node reboot.

11.14.6.44. RxDataPollCount Attribute

This attribute SHALL indicate the total number of received unique MAC Data Poll frames. This value SHALL only be reset upon a Node reboot.

11.14.6.45. RxBeaconCount Attribute

This attribute SHALL indicate the total number of received unique MAC Beacon frames. This value SHALL only be reset upon a Node reboot.

11.14.6.46. RxBeaconRequestCount Attribute

This attribute SHALL indicate the total number of received unique MAC Beacon Request frames. This value SHALL only be reset upon a Node reboot.

11.14.6.47. RxOtherCount Attribute

This attribute SHALL indicate the total number of received unique MAC frame requests that are not counted by any other attribute. This value SHALL only be reset upon a Node reboot.

11.14.6.48. RxAddressFilteredCount Attribute

This attribute SHALL indicate the total number of received unique MAC frame requests that have been dropped as a result of MAC filtering. This value SHALL only be reset upon a Node reboot.

11.14.6.49. RxDestAddrFilteredCount Attribute

This attribute SHALL indicate the total number of received unique MAC frame requests that have been dropped as a result of a destination address check. This value SHALL only be reset upon a Node reboot.