

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
1	NodeID	node-id	all				M
2	Endpoint	endpoint-no	all				M

FabricIndex Field

The [Fabric Index](#) associated with the Fabric of the client which last set the value of the trusted time source node.

NodeID Field

Node ID of the trusted time source node on the Fabric associated with the entry.

Endpoint Field

Endpoint on the trusted time source node that contains the Time Synchronization cluster server.

11.17.6.5. FabricScopedTrustedTimeSourceStruct Type

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	NodeID	node-id	all				M
1	Endpoint	endpoint-no	all				M

NodeID Field

Node ID of the trusted time source node on the Fabric of the issuer.

Endpoint Field

Endpoint on the trusted time source node that contains the Time Synchronization cluster server. This is provided to avoid having to do discovery of the location of that endpoint by walking over all endpoints and checking their [Descriptor Cluster](#).

11.17.6.6. TimeZoneStruct Type

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Offset	int32	-43200 to 50400				M
1	ValidAt	epoch-us	all				M
2	Name	string	0 to 64				O