

11.17.8.1. UTCTime Attribute

If the node has achieved time synchronization, this attribute SHALL indicate the current time as a UTC [epoch-us](#) (Epoch Time in Microseconds).

If the node has not achieved time synchronization, this attribute SHALL be null. This attribute MAY be set when a [SetUTCTime](#) is received.

11.17.8.2. Granularity Attribute

This attribute SHALL indicate granularity of the error that the node is willing to guarantee on the time synchronization. It is of type [GranularityEnum](#).

This value SHALL be set to NoTimeGranularity if UTCTime is null and SHALL NOT be set to NoTimeGranularity if UTCTime is non-null.

11.17.8.3. TimeSource Attribute

This attribute SHALL indicate the node's time source. This attribute indicates what method the node is using to sync, whether the source uses NTS or not and whether the source is internal or external to the Matter network. This attribute MAY be used by a client to determine its level of trust in the UTCTime. It is of type [TimeSourceEnum](#).

If a node is unsure if the selected NTP server is within the Matter network, it SHOULD select one of the NonMatter* values.

This value SHALL be set to None if UTCTime is null and SHALL NOT be set to None if UTCTime is non-null.

11.17.8.4. TrustedTimeSource Attribute

This attribute SHALL indicate the Node ID, endpoint, and associated [fabric index](#) of a Node that MAY be used as trusted time source. See [Section 11.17.13, "Time source prioritization"](#). This attribute reflects the last value set by an administrator using the [SetTrustedTimeSource](#) command. If the value is null, no trusted time source has yet been set.

11.17.8.5. DefaultNTP Attribute

This attribute SHALL indicate the default NTP server that this Node MAY use if other time sources are unavailable. This attribute is settable by an Administrator using the [SetDefaultNTP](#) command. It SHOULD be set by the Commissioner during commissioning. If no default NTP server is available, the Commissioner MAY set this value to null. The default IANA assigned NTP port of 123 SHALL be used to access the NTP server.

If set, the format of this attribute SHALL be a domain name or a static IPv6 address with no port, in text format, as specified in [RFC 5952](#). The address format SHALL follow the recommendations in Section 4 and SHALL NOT contain a port number.

11.17.8.6. TimeZone Attribute

This attribute SHALL contain a list of time zone offsets from UTC and when they SHALL take effect.