

This attribute uses a list of time offset configurations to allow Nodes to handle scheduled regulatory time zone changes. This attribute SHALL NOT be used to indicate daylight savings time changes (see [Section 11.17.8.7, “DSTOffset Attribute”](#) for daylight savings time).

The first entry SHALL have a ValidAt entry of 0. If there is a second entry, it SHALL have a non-zero ValidAt time.

If a node supports a [TimeZoneDatabase](#), and it has data for the given time zone Name and the given Offset matches, the node MAY update its own [DSTOffset](#) attribute to add new DST change times as required, based on the Name fields of the TimeZoneStruct. Administrators MAY add additional entries to the DSTOffset of other Nodes with the same time zone, if required.

If a node does not support a [TimeZoneDatabase](#), the Name field of the [TimeZoneStruct](#) is only applicable for client-side localization. In particular:

- If the node does not support a [TimeZoneDatabase](#), the Name field SHALL NOT be used to calculate the local time.
- If the node does not support a [TimeZoneDatabase](#), the Name field SHALL NOT be used to calculate DST start or end dates.

When time passes, the node SHOULD remove any entries which are no longer active and change the ValidAt time for the currently used TimeZoneStruct list item to zero.

This attribute SHALL have at least one entry. If the node does not have a default time zone and no time zone has been set, it MAY set this value to a list containing a single [TimeZoneStruct](#) with an offset of 0 (UTC) and a ValidAt time of 0.

11.17.8.7. DSTOffset Attribute

This attribute SHALL contain a list of offsets to apply for daylight savings time, and their validity period.

List entries SHALL be sorted by ValidStarting time.

A list entry SHALL NOT have a ValidStarting time that is smaller than the ValidUntil time of the previous entry. There SHALL be at most one list entry with a null ValidUntil time and, if such an entry is present, it SHALL appear last in the list.

Over time, the node SHOULD remove any entries which are no longer active from the list.

Over time, if the node supports a [TimeZoneDatabase](#) and it has information available for the given time zone name, it MAY update its own list to add additional entries.

If a time zone does not use DST, this SHALL be indicated by a single entry with a 0 offset and a null ValidUntil field.

11.17.8.8. LocalTime Attribute

This attribute SHALL indicate the computed current local time of the node as a [epoch-us](#) (Epoch Time in Microseconds). The value of LocalTime SHALL be the sum of the [UTCTime](#), the offset of the currently valid [TimeZoneStruct](#) from the [TimeZone](#) attribute (converted to microseconds), and the