

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Offset	int32	-43200 to 50400			M
1	Name	string	0 to 64			O

Offset Field

Current time zone offset from UTC in seconds.

Name Field

Current time zone name. This name SHOULD use the country/city format specified by the [IANA Time Zone Database](#).

11.17.10.4. TimeFailure Event

This event SHALL be generated if the node has not generated a TimeFailure event in the last hour, and the node is unable to get a time from any source. This event SHOULD NOT be generated more often than once per hour.

11.17.10.5. MissingTrustedTimeSource Event

This event SHALL be generated if the TrustedTimeSource is set to null upon fabric removal or by a [SetTrustedTimeSource](#) command.

This event SHALL also be generated if the node has not generated a MissingTrustedTimeSource event in the last hour, and the node fails to update its time from the TrustedTimeSource because the TrustedTimeSource is null or the specified peer cannot be reached. MissingTrustedTimeSource events corresponding to a time update SHOULD NOT be generated more often than once per hour.

11.17.11. Time Synchronization at Commissioning

During commissioning the Commissioner SHOULD set the UTCTime, and set up the TrustedTimeSource, DefaultNTP, TimeZone and DSTOffsets as required. See [Commissioning Flows](#). Note that the commissioner MAY opt to not set the time so the node SHOULD NOT depend on having time during commissioning.

11.17.12. Time Synchronization during operation

Nodes MAY perform time synchronization using a trusted external source, [RFC 5905](#) or by reading the UTC time from the Time Synchronization cluster of another Node with the desired Granularity and TimeSource. When using NTPv4 / SNTPv4, Nodes capable of external communication SHOULD use network time security (NTS) if that is available on the server ([RFC 8915](#)). This specification DOES NOT mandate that Nodes should include a TCP/TLS stack and a set of adequate Root CA certificates solely to support NTS, but that if a Node already has these capabilities, then it SHOULD implement and attempt NTS for NTP.

Nodes SHOULD attempt to perform a time synchronization after a restart or upon any change of