

11.18.4.4. NOCStruct Type

This encodes a [NOC](#) chain, underpinning a commissioned Operational Identity for a given Node.

Access Modifier: Fabric Scoped							
ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
1	NOC	octstr	max 400				M
2	ICAC	octstr	max 400	X			M
3	VVSC	octstr	max 400				desc

NOTE

The VVSC field is mutually exclusive with the ICAC field. If the ICAC field is non-null, the VVSC field SHALL be omitted. If the VVSC field is present in the structure, the ICAC field SHALL be null. The reason for this is to optimize storage usage, as the VID Verification Signer Certificate (VVSC) is a field that is only needed in root-per-fabric situations without ICAC present.

NOTE

The [Trusted Root CA Certificate \(RCAC\)](#) is not included in this structure. The roots are available in the [TrustedRootCertificates attribute](#) under the same [associated fabric](#) as the one for the NOCStruct entry.

NOC Field

This field SHALL contain the [NOC](#) for the struct's [associated fabric](#), encoded using [Matter Certificate Encoding](#).

ICAC Field

This field SHALL contain the [ICAC](#) for the struct's [associated fabric](#), encoded using [Matter Certificate Encoding](#). If no ICAC is present in the chain, this field SHALL be set to null.

VVSC Field

This field SHALL contain the [Vendor Verification Signer Certificate \(VVSC\)](#) for the struct's [associated fabric](#), encoded using [Matter Certificate Encoding](#). If no VVSC is needed, this field SHALL be omitted (in that there SHALL NOT be a value present, not even an empty octet string). If the ICAC field is non-null, this field SHALL NOT be present.

11.18.4.5. FabricDescriptorStruct Type

Access Modifier: Fabric Scoped							
ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
1	RootPublicKey	octstr	65				M
2	VendorID	vendor-id	desc				M