

```

csr[1]                : OCTET STRING,
CSRNonce[2]           : OCTET STRING [ length 32 ],
vendor_reserved1[3, optional] : OCTET STRING,
vendor_reserved2[4, optional] : OCTET STRING,
vendor_reserved3[5, optional] : OCTET STRING
}

```

Any context-specific tags not listed in the above schema for NOCSR Elements SHALL be reserved for future use, and SHALL be silently ignored if seen by a Commissioner which cannot understand them.

11.18.4.9. NOCSR Information

The NOCSR Information is the combination of a [Matter TLV](#) payload, containing the [NOCSR Elements](#), as well as a signature over an `nocsr_tbs` message containing the in-band-transmitted `nocsr_elements_message` and a secret out-of-band Attestation Challenge, using the Attestation Private Key that is unique to the device producing the NOCSR Information.

The NOCSR Information SHALL be computed as follows:

1. Encode the [nocsr-elements](#) structure with an anonymous tag into an octet string called `nocsr_elements_message`.
 - The `csr` field SHALL be a DER-encoded octet string of a properly encoded [PKCS #10](#) Certificate Signing Request (CSR), signed with the [Node Operational Private Key](#) associated with the Node Operational Public Key, which is the `subjectPublicKey` field of the CSR. See [Section 6.4.6.1, “Node Operational Certificate Signing Request \(NOCSR\) Procedure”](#) for details about the generation of the Node Operational Key Pair, and the contents of the CSR.
 - The `CSRNonce` field SHALL match the CSR Nonce field in the corresponding [CSRRequest Command](#).
 - The `vendor_reserved1` through `vendor_reserved3` fields allow the Node taking part in the NOCSR Procedure to communicate vendor-specific information that MAY aid in device commissioning. Commissioners that do not understand the format of the data MAY ignore them.
 - The resulting `nocsr_elements_message`, including optional fields, SHALL be no more than [RESP_MAX](#) bytes once serialized.

```

nocsr_elements_message =
{
    csr(1)      = node_operational_csr_der_bytes,
    CSRNonce(2) = CSRNonce,

    ... optional fields per nocsr-elements ..
}

```

2. Obtain the AttestationChallenge from a [CASE session](#), [resumed CASE session](#), or [PASE session](#)