

- depending on the method used to establish the current session. This is an octet string of length `CRYPTO_SYMMETRIC_KEY_LENGTH_BITS`. Save it for the next step as `attestation_challenge`.
- Locally generate an `nocsr_tbs` message as an octet string by concatenating the `nocsr_elements_message` and the `attestation_challenge`:
 - `nocsr_tbs = nocsr_elements_message || attestation_challenge`
 - Compute the `attestation_signature` and record it as an `ec-signature` octet string:

```
attestation_signature = Crypto_Sign(  
    message = nocsr_tbs,  
    privateKey = Device Attestation Private Key  
)
```

- Fill the `NOCSRElements` field of the `CSRResponse Command` using the contents of the `nocsr_elements_message` octet string.
- Fill the `AttestationSignature` field of the `CSRResponse Command` using the contents of the `attestation_signature` octet string.
- Note that the `attestation_challenge` SHALL NOT be included in any of the payloads conveyed as part of the `NOCSR Information`.

See [Section F.3, “Node Operational CSR Response test vector”](#) for an example computation of the above messages and application payloads.

11.18.5. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	NOCs	list[NOC-Struct]	max SupportedFabrics	C N		R A F	M
0x0001	Fabrics	list[FabricDescriptorStruct]	max SupportedFabrics	N		R V F	M
0x0002	SupportedFabrics	uint8	5 to 254	F		R V	M
0x0003	Commissioned-Fabrics	uint8	max SupportedFabrics	N		R V	M
0x0004	Trusted-RootCertificates	list[octstr]	max SupportedFabrics[max 400]	C N		R V	M