

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	NOCValue	octstr	max 400			M
1	ICACValue	octstr	max 400			O
2	IPKValue	octstr	16			M
3	CaseAdmin-Subject	subject-id				M
4	AdminVendorId	vendor-id				M

IPKValue Field

This field SHALL contain the value of the Epoch Key for the Identity Protection Key (IPK) to set for the Fabric which is to be added. This is needed to bootstrap a necessary configuration value for subsequent [CASE](#) to succeed. See [Section 4.14.2.6.1, “Identity Protection Key \(IPK\)”](#) for details.

The IPK SHALL be provided as an octet string of length CRYPTO_SYMMETRIC_KEY_LENGTH_BYTES.

On successful execution of the AddNOC command, the side-effect of having provided this field SHALL be equivalent to having done a [GroupKeyManagement](#) cluster [KeySetWrite](#) command invocation using the newly joined fabric as the [accessing fabric](#) and with the following argument fields (assuming KeySetWrite allowed a GroupKeySetID set to 0):

```

KeySetWrite
(
    GroupKeySetStruct :=
    {
        GroupKeySetID := 0,
        GroupKeySecurityPolicy := 0,
        EpochKey0 := <Contents of IPKValue field>,
        EpochStartTime0 := 0,
        EpochKey1 := null
        EpochStartTime1 := null
        EpochKey2 := null,
        EpochStartTime2 := null
    }
)

```

CaseAdminSubject Field

If the AddNOC command succeeds according to the semantics of the following subsections, then the Access Control [subject-id](#) SHALL be used to atomically add an [Access Control Entry](#) enabling that Subject to subsequently administer the Node whose operational identity is being added by this command.