

testing), or provide dedicated Software Images to a subset of Nodes to affect particular diagnosis tasks, etc. The mechanism described in this cluster is not particularly well-suited for such fine-grained deployment (unless the OTA Provider is provided by, or associated with, the Manufacturer).

To achieve more targeted roll-out, Vendors MAY commission a Node on the same Fabric as the devices requiring the special rules, so that it MAY provide OTA Provider capabilities beyond the core interoperable aspects of this Cluster. Finer-grained selection MAY be applied by special OTA Software Image Selection logic in a given OTA Provider, using the [MetadataForProvider](#) field and [MetadataForRequestor](#) fields of the [QueryImage](#) command. Furthermore, such special OTA Provider may identify itself by including the [MetadataForNode](#) field in a given [AnnounceOTAProvider](#) command.

If such a special Software Image is running on an OTA Requestor, the OTA Requestor MAY reject Software Images provided to it by an OTA Provider on the Fabric, to prevent loss of the non-standard Software Image. A Factory Data Reset of the OTA Requestor SHALL remove such override.

11.20.5.3. Other considerations

While it is expected that Nodes fulfilling the role of OTA Provider will likely have high availability within the Fabric, it may be possible some will be battery-operated or be power-cycled frequently. It is RECOMMENDED that an OTA Provider Node that determines it cannot reliably stay available to service OTA Requestors SHOULD avoid responding with an available OTA Software Image when responding to a QueryImage command (see [Section 11.20.6.5.2, “QueryImageResponse Command”](#)) unless it has sufficient availability to allow a long-running [BDX Protocol](#) transfer to finish. In general, OTA Provider role SHOULD be fulfilled by a Node with a reliable network availability and stable power, especially if it is set as a default in the [DefaultOTAProviders](#) attribute.

11.20.6. OTA Software Update Provider Cluster

This cluster implements the Provider role in the OTA process.

11.20.6.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision

11.20.6.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Utility	Node	OTAP

11.20.6.3. Cluster ID