

DelayedActionTime Field

The minimum time period the OTA Requestor SHALL wait before executing the Action, in seconds from receipt.

If this field has a value higher than 86400 seconds (24 hours), then the OTA Requestor MAY assume a value of 86400, in order to reduce undue Software Image application delays.

NotifyUpdateApplied Command

This command tells the Provider that the specified update has been applied.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	UpdateToken	octstr	8 to 32			M
1	SoftwareVersion	uint32	all			M

UpdateToken Field

This field SHALL contain the UpdateToken as specified in [Section 11.20.3.6.1, “UpdateToken usage”](#).

SoftwareVersion Field

The SoftwareVersion included in the request payload SHALL provide the same value as the [SoftwareVersion](#) attribute in the invoking OTA Requestor’s [Basic Information Cluster](#), and SHOULD be consistent with the value representing a new version running on the Node invoking the command.

When Generated

The NotifyUpdateApplied command SHOULD be invoked in the following two circumstances:

1. An OTA Requestor has just successfully applied a Software Image it had obtained from a previous [QueryImageResponse](#).
2. An OTA Requestor has just successfully applied a Software Image it had obtained through means different than those of this Cluster.

An OTA Provider MAY use the state of invocation of this command to help track the progress of update for OTA Requestors it knows require a new OTA Software Image. However, due to the possibility that an OTA Requestor MAY never come back (e.g. device removed from Fabric altogether, or a critical malfunction), an OTA Provider SHALL NOT expect every OTA Requestor to invoke this command for correct operation of the OTA Provider.

This command SHALL be considered optional and SHALL NOT result in reduced availability of the OTA Provider functionality if OTA Requestors never invoke this command.