

ID	Name	Direction	Response	Access	Conformance
0x00	AnnounceOTAProvider	client ⇒ server	Y	A	O

AnnounceOTAProvider Command

This command MAY be invoked by Administrators to announce the presence of a particular OTA Provider.

This command SHALL be [scoped](#) to the [accessing fabric](#).

If the [accessing fabric index](#) is 0, this command SHALL fail with an UNSUPPORTED_ACCESS status code.

Access Modifier: Fabric Scoped						
ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ProviderNodeID	node-id				M
1	VendorID	vendor-id				M
2	AnnouncementReason	AnnouncementReasonEnum				M
3	MetadataForNode	octstr	max 512			O
4	Endpoint	endpoint-no				M

ProviderNodeID Field

This field SHALL contain the [Node ID](#) of a Node implementing the OTA Provider cluster server, on the [accessing fabric](#).

VendorID Field

This field SHALL contain the assigned Vendor ID of the Node invoking this command, as it would appear in that Node's [Basic Information Cluster VendorID](#) attribute.

AnnouncementReason Field

This field SHALL contain a value expressing the reason for the announcement.

MetadataForNode Field

This optional field, if present, SHALL consist of a [top-level anonymous list](#); each list element SHALL have a [profile-specific](#) tag encoded in [fully-qualified](#) form. Each list element SHALL contain a manufacturer-specific payload, which the Node invoking this command wants to expose to the receiving