

11.21.2.3. HeaderSize field

The HeaderSize field is fixed-width, little-endian-encoded, unsigned 32-bit value that SHALL indicate the total size, in bytes, of the TLV-encoded Header field.

11.21.2.4. Header field

The Header is a [TLV](#) structure, encoded with anonymous outer tag, with the following format:

```
ota-image-header-struct => STRUCTURE [ tag-order ]
{
  VendorID           [0] : UNSIGNED INTEGER [ range 16bits ],
  ProductID          [1] : UNSIGNED INTEGER [ range 16bits ],
  SoftwareVersion     [2] : UNSIGNED INTEGER [ range 32bits ],
  SoftwareVersionString [3] : STRING [ length 1..64 ],
  PayloadSize        [4] : UNSIGNED INTEGER [ range 64bits ],
  MinApplicableSoftwareVersion [5, optional] : UNSIGNED INTEGER [ range 32bits ],
  MaxApplicableSoftwareVersion [6, optional] : UNSIGNED INTEGER [ range 32bits ],
  ReleaseNotesURL     [7, optional] : STRING [ length 1..256 ],
  ImageDigestType     [8] : UNSIGNED INTEGER [ range 8bits ],
  ImageDigest         [9] : OCTET STRING [ length 0..64 ]
}
```

VendorID field

The VendorID field SHALL be used by an OTA Provider to determine if a Node is the intended recipient of the OTA software update file by checking that the VendorID field in the OTA software update file matches the [VendorID](#) received in the [Query Image command](#) from the OTA Requestor. This VendorID field MAY be zero, in which case this OTA software update file MAY apply to more than one vendor.

ProductID field

The ProductID field MAY be used by an OTA Provider to determine if a Node is the intended recipient of the OTA software update file by checking that the ProductID field in the OTA software update file matches the [ProductID](#) received in the [Query Image command](#) from the OTA Requestor. This ProductID field MAY be zero, in which case this OTA software update file MAY apply to more than one product.

SoftwareVersion field

The SoftwareVersion field SHALL contain the version for the software contained within the file. A larger value of SoftwareVersion is newer than a lower value. The SoftwareVersion value SHOULD NOT be displayed to an end-user.

For a given version, this SoftwareVersion field SHALL match what the Node will report in its [SoftwareVersion](#) attribute in the [Basic Information Cluster](#), once executing the version.