

11.22.2.8. BDX Session

A bulk data transfer Session is a series of messages passed between a Sender and Receiver that begins with the Initiator starting the transfer negotiation, and ends with a **BlockAckEOF** from the Receiver which indicates receipt of all transmitted data and ends the session. All messages in a session SHALL be sent within the scope of a single **Exchange**. Only one bulk data transfer session can be in progress at any time during a **Exchange**.

11.22.3. Protocol Opcodes and Status Report Values

11.22.3.1. BDX Protocol Messages

Each message in the BDX protocol is mapped to a unique **Protocol Opcode**, namespaced under the **PROTOCOL_ID_BDX Protocol ID**:

- **Vendor ID** = 0x0000 (Matter Common)
- **Protocol ID** = **PROTOCOL_ID_BDX**

Table 108. BDX Protocol Opcodes

Protocol Opcode	Message
0x01	SendInit
0x02	SendAccept
0x03	Reserved for future use
0x04	ReceiveInit
0x05	ReceiveAccept
0x06 ... 0x0F	Reserved for future use
0x10	BlockQuery
0x11	Block
0x12	BlockEOF
0x13	BlockAck
0x14	BlockAckEOF
0x15	BlockQueryWithSkip

11.22.3.2. BDX Status Codes

The list of status codes used in **StatusReport** messages to signify a reason for failing or rejecting a transfer is provided in Table 109, “BDX Status reports”. For **StatusReport** messages, the protocol needs to be defined as the BDX protocol, i.e. **StatusReport**(GeneralCode: FAILURE, ProtocolId: {VendorID=0x0000, ProtocolId=BDX}, ProtocolCode: <value>).

Table 109. BDX Status reports