

per [Table 109, “BDX Status reports”](#).

Possible replies for **SendInit** (See [Section 11.22.7, “Synchronous Transfers Message Flows”](#) for examples):

- Success: **SendAccept**, if the transfer is accepted by the Responder
- Failure: **StatusReport**(GeneralCode: **FAILURE**, ProtocolId: **BDX**, ProtocolCode: **<error-specific>**), if the transfer is rejected by the Responder, or anything that prevents the Responder from being able to proceed with the transfer as requested.
 - **FILE_DESIGNATOR_UNKNOWN**: The **file designator** field was present and contained a file designator not supported by the responder.
 - **START_OFFSET_NOT_SUPPORTED**: The **start offset** field contained an invalid start offset, or presence of start offset indicated by **RC[STARTOFS]** is not supported by the responder.
 - **LENGTH_TOO_LARGE**: The **definite length** field was present, but too large for the responder.
 - **LENGTH_TOO_SHORT**: The **definite length** field was present, but contextually too short based on the responder’s knowledge of expected size.
 - **LENGTH_REQUIRED**: The responder can only support the proposed transfer if the **definite length** field is provided.
 - **TRANSFER_METHOD_NOT_SUPPORTED**: The responder does not support the proposed transfer control method.
 - **RESPONDER_BUSY**: The responder is too busy to process another transfer. An initiator SHOULD wait at least 60 seconds before attempting to initiate a new **SendInit** with this responder.

Possible replies for **ReceiveInit** (See [Section 11.22.7, “Synchronous Transfers Message Flows”](#) for examples):

- Success: **ReceiveAccept**, if the transfer is accepted by the Responder
- Failure: **StatusReport**(GeneralCode: **FAILURE**, ProtocolId: **PROTOCOL_ID_BDX**, ProtocolCode: **<error-specific>**), if the transfer is rejected by the Responder, or anything that prevents the Responder from being able to proceed with the transfer as requested:
 - **FILE_DESIGNATOR_UNKNOWN**: The **file designator** field was present and contained a file designator not found or supported by the responder.
 - **START_OFFSET_NOT_SUPPORTED**: The **start offset** field contained an invalid start offset, or presence of start offset indicated by **RC[STARTOFS]** is not supported by the responder.
 - **LENGTH_TOO_LARGE**: The **definite length** field was present, but too large for the responder.
 - **LENGTH_REQUIRED**: The responder can only support the proposed transfer if the **definite length** field is provided.
 - **TRANSFER_METHOD_NOT_SUPPORTED**: The responder does not support the proposed transfer control method.
 - **RESPONDER_BUSY**: The responder is too busy to process another transfer. An initiator SHOULD wait at least 60 seconds before attempting to initiate a new **ReceiveInit** with this responder.