

The format of the **SendInit** and **ReceiveInit** messages is enumerated in Table 110, “**SendInit/ReceiveInit message fields**”.

Table 110. *SendInit/ReceiveInit message fields*

Field	Size	Notes
Message ID: SendInit (0x01), ReceiveInit (0x04)		
Proposed Transfer Control (PTC)	1 octet	
Range Control (RC)	1 octet	
Proposed Max Block Size (PMBS)	2 octets	Unsigned little-endian
Start Offset (STARTOFS)	4/8 octets	Optional. • Present if RC[STARTOFS] = 1 • Size = 4 if RC[WIDERANGE] = 0 • Size = 8 if RC[WIDERANGE] = 1
Proposed Max Length (LEN)	4/8 octets	Optional. • Present if RC[DEFLN] = 1 • Size = 4 if RC[WIDERANGE] = 0 • Size = 8 if RC[WIDERANGE] = 1
File Designator Length (FDL)	2 octets	Unsigned little-endian
File Designator (FD)	variable length	
Metadata (MDATA)	variable	Optional, TLV.

The following subsections describe the fields composing the **SendInit** and **ReceiveInit** messages.

Proposed Transfer Control (**PTC**)

The Proposed Transfer Control (**PTC**) field specifies, as subfields, the highest version of the protocol and the transfer modes supported by the Initiator of the transfer. All PTC subfields are Initiator-proposed. It is up to the Responder to decide what version and modes it will use. The first version, as of Matter specification 1.0 is BDX Version 0.

At least one of the **PTC**[**RECEIVER_DRIVE**] or **PTC**[**SENDER_DRIVE**] field bits SHALL be set in order for the Responder to set the final transfer control. If neither **PTC**[**RECEIVER_DRIVE**] or **PTC**[**SENDER_DRIVE**] is set, the transfer SHALL be rejected by the Responder.