

fields”.

Since the meaning of many fields overlap in these messages, they are described only once following the ReceiveAccept message fields.

Table 113. SendAccept message fields

Field	Size	Notes
Message ID: SendAccept(0x02)		
Transfer Control (TC)	1 octet	Must specify at least one of: • TC[RECEIVER_DRIVE] • TC[SENDER_DRIVE] and optionally: • TC[ASYNC] (NOTE: Support for the asynchronous mode is provisional)
Max Block Size (MBS)	2 octets	Unsigned little-endian. Must be $\leq$ PMBS .
Metadata (MDATA)	variable	Optional, TLV.

Table 114. ReceiveAccept message fields

Field	Size	Notes
Message ID: ReceiveAccept(0x05)		
Transfer Control (TC)	1 octet	Must specify exactly one of: • TC[ASYNC] • TC[RECEIVER_DRIVE] • TC[SENDER_DRIVE]
Range Control (RC)	1 octet	
Max Block Size (MBS)	2 octets	Unsigned little-endian. Must be $\leq$ PMBS .
Length (LEN)	4/8 octets	Optional. • Present if RC[DEFLLEN] = 1 • Size = 4 if RC[WIDERANGE] = 0 • Size = 8 if RC[WIDERANGE] = 1
Metadata (MDATA)	variable	Optional, TLV.

The following subsections describe the fields composing the **SendAccept** and **ReceiveAccept** mes-