

SendAccept/ReceiveAccept TC[ASYNC]: asynchronous mode enabled

- Width: 1 bit
- Values:
 - 0 if synchronous mode was chosen for the transfer.
 - 1 if asynchronous mode was chosen for the transfer.
 - NOTE: Synchronous mode is always implicitly supported.
 - NOTE: Support for the asynchronous mode is provisional and SHALL not be chosen by the Responder.

ReceiveAccept Range Control (RC)

NOTE

This field is only present in **ReceiveAccept** messages.

The Range Control (RC) field specifies parameters related to offset and length of the transfer:

- whether the transfer has a definite length (**DEFLEN**);
- the width of the length and offset fields (**WIDERANGE**).

Table 116. *ReceiveAccept Range Control (RC) field structure*

bit 7	6	5	4	3	2	1	0
RFU			WIDERANGE	RFU			DEFLEN

The fields for **RC** are:

ReceiveAccept RC[DEFLEN]: definite length present

- Width: 1 bit
 - Values:
 - 0 if no length is present (indefinite length)
 - 1 if a definite length is present (see [Section 11.22.5.4.4](#), “Length (LEN)”)

ReceiveAccept RC[WIDERANGE]: wide (64-bit) range enable for values

- Width: 1 bit
 - Values:
 - 0 to indicate that length **LEN** is a 4 octets (32-bit) little-endian unsigned quantity.
 - 1 to indicate that length **LEN** is a 8 octets (64-bit) little-endian unsigned quantity.

Max Block Size (MBS)

The Max Block Size (**MBS**) field specifies the maximum size, in bytes, of each block for this transfer. The maximum whole block payload size will be the sum of the Max Block Size and the size of the block parameters (such as the block counter). This value SHALL be less than or equal to the [pro-](#)