

SHALL be enforced against the tuple containing all of:

- VendorID
- Label
- IssuerSubjectKeyID

Therefore, there MAY be multiple entries for the same VendorID and IssuerSubjectKeyID in case partitioning is done, which are disambiguated by the Label.

Enforcement of uniqueness constraints SHALL be done by the Distributed Compliance Ledger's block transaction processing and SHALL also be done by clients making use of the information from this schema.

#### 11.23.9.5. CRLSignerDelegator

This field SHALL be present and non-empty if all of the following are true:

- Certificate in CRLSignerCertificate field is not self-signed.
- IsPAA is false.
- CRLSignerCertificate is not a PAI.

When present, this field SHALL contain the issuer certificate which signed the CRLSignerCertificate, encoded in X.509v3 PEM format.

Additional constraints related to the value of this field are specified in [Section 11.23.9.6, "CRLSignerCertificate"](#).

#### 11.23.9.6. CRLSignerCertificate

This field SHALL contain the issuer certificate who signed the revocation information that is provided in the distribution point entry, encoded in X.509v3 PEM format.

If the RevocationType is **1** (X.509v3 CRL):

- The certificate's subject public key SHALL be used to validate the **signatureValue** of the **CertificateList** object in the CRL (see [RFC 5280](#) sec 5.1.1.3). These checks SHALL be done by the client making use of the information, since they cannot be done by the Distributed Compliance Ledger implementation which cannot rely on out-of-ledger records or files.
- The certificate's **SubjectKeyIdentifier** mandatory extension SHALL match the **Authority Key Identifier** found in the file at the **DataUrl**.
- The certificate SHALL be checked for correct chaining by the dynamic validation within the Distributed Compliance Ledger's block transaction processing:
  - If the certificate is self-signed, it SHALL be considered as a PAA certificate, the **IsPAA** field SHALL be true, and the certificate SHALL be found in the list of approved PAA certificates currently in force in the Distributed Compliance Ledger using exact byte equality.
  - If the certificate is not self-signed and the **IsPAA** field is set to true, it SHALL be considered as a CRL signer certificate delegated by a PAA. The certificate format SHALL be as specified in