

Section 11.23.9.6.1, “PAA-delegated CRLSignerCertificate format”. The certificate SHALL be validated using the set of approved PAA certificates currently in force in the Distributed Compliance Ledger and the **IssuerSubjectKeyID** field SHALL match the **SubjectKeyIdentifier** extension value in the matching PAA. Commissioners SHALL verify that the PAA that issued the CRLSignerCertificate is the same PAA that issued the PAI being checked for revocation.

- If the certificate is not self-signed and the **IsPAA** field is set to false, it SHALL be considered as a PAI certificate or a CRL signer certificate delegated by a PAI. The format of a CRL signer certificate delegated by a PAI SHALL be as specified in Section 11.23.9.6.2, “PAI-delegated CRLSignerCertificate format”. If the CRL signer certificate is not a PAI certificate but is delegated by a PAI, then the PAI certificate SHALL be present in the CRLSignerDelegator field so that the full certificate chain can be verified. The certification path containing the certificate SHALL be validated using the set of approved PAA certificates currently in force in the Distributed Compliance Ledger as the trust store. Commissioners SHALL verify that either the CRLSignerCertificate or the CRLSignerDelegator is the same PAI that issued the DAC being checked for revocation.

PAA-delegated CRLSignerCertificate format

In case the CRLSignerCertificate is a delegate of a PAA for signing CRL for revoking PAI certificates, then the certificate SHALL follow the following constraints layered on top of the encoding specified by RFC 5280 within the **TBSCertificate** structure:

1. The **version** field SHALL be set to **2** to indicate v3 certificate.
2. The **signature** field SHALL contain the identifier for signatureAlgorithm **ecdsa-with-SHA256**.
3. The **issuer** field SHALL be a sequence of **RelativeDistinguishedName** s.
4. The **issuer** field SHALL match the **subject** field of the parent PAA certificate.
5. The **subject** field SHALL be a sequence of **RelativeDistinguishedName** s.
6. A ProductID value SHALL NOT be present in either the **subject** or **issuer** fields.
7. The algorithm field in **subjectPublicKeyInfo** field SHALL be the object identifier for **prime256v1**.
8. The certificate SHALL carry the following Extensions:
 - a. Basic Constraint extension SHALL be marked **critical** and have the **CA** field set to FALSE.
 - b. Key Usage extension SHALL be marked **critical**.
 - i. The **cRLSign** bits SHALL be set in the **KeyUsage** bitstring
 - ii. The **digitalSignature** bit MAY be set in the **KeyUsage** bitstring
 - iii. Other bits SHALL NOT be set
 - c. Subject Key Identifier
9. The certificate MAY also carry the following additional Extensions:
 - a. Extended Key Usage
 - b. Authority Key Identifier
 - c. Any other extension allowed in RFC 5280 where inclusion does not violate size limitations. These extensions insofar not defined in this specification SHALL be ignored, but MAY be