

present to allow flexibility in CA operation.

PAI-delegated CRLSignerCertificate format

In case the CRLSignerCertificate is a delegate of a PAI for signing CRL for revoking DAC certificates, then the certificate SHALL follow the following constraints layered on top of the encoding specified by [RFC 5280](#) within the [TBSCertificate](#) structure:

1. The [version](#) field SHALL be set to [2](#) to indicate v3 certificate.
2. The [signature](#) field SHALL contain the identifier for signatureAlgorithm [ecdsa-with-SHA256](#).
3. The [issuer](#) field SHALL be a sequence of [RelativeDistinguishedName](#) s.
4. The [issuer](#) field SHALL match the [subject](#) field of the parent PAI certificate.
5. The [subject](#) field SHALL be a sequence of [RelativeDistinguishedName](#) s.
6. The algorithm field in [subjectPublicKeyInfo](#) field SHALL be the object identifier for [prime256v1](#).
7. The certificate SHALL carry the following Extensions:
 - a. Basic Constraint extension SHALL be marked [critical](#) and have the [ca](#) field set to FALSE.
 - b. Key Usage extension SHALL be marked [critical](#)
 - i. The [cRLSign](#) bit SHALL be set in the [KeyUsage](#) bitstring
 - ii. The [digitalSignature](#) bit MAY be set in the [KeyUsage](#) bitstring
 - iii. Other bits SHALL NOT be set
 - c. Authority Key Identifier
 - d. Subject Key Identifier
8. The certificate MAY also carry the following additional Extensions:
 - a. Extended Key Usage
 - b. Any other extension allowed in [RFC 5280](#) where inclusion does not violate size limitations. These extensions insofar not defined in this specification SHALL be ignored, but MAY be present to allow flexibility in CA operation.

11.23.9.7. IssuerSubjectKeyID

This field SHALL uniquely identify the PAA or PAI for which this revocation distribution point is provided, via the certificate's [SubjectKeyIdentifier](#) mandatory extension. This field is provided to assist queries without requiring additional certificate parsing. This field SHALL provide the subject key identifier as an even number of uppercase hexadecimal characters ([\[0-9A-F\]](#)), with no white-space and no non-hexadecimal characters.

For example, subject key ID [A3:03:13:6D:54:A8:4B:E2:4C:48:87:B3:41:06:6D:C2:70:96:2F:99](#) (as it would appear in [openssl x509](#) output, for human consumption) would be recorded as [A303136D54A84BE24C4887B341066DC270962F99](#).

When processing revocation information during the device [Device Attestation Procedure](#), clients SHALL only use entries whose [IssuerSubjectKeyID](#) matches a candidate certificate's Authority Key Identifier extension.