

11.23.9.11. DataDigestType

This field, if present, SHALL indicate the type of digest used in the DataDigest field. This field SHALL be provided if and only if the DataDigest field is present.

The value of this field SHALL be a supported numerical identifier value from the [IANA Named Information Hash Algorithm Registry](https://www.iana.org/assignments/named-information/named-information.xhtml#hash-alg) [https://www.iana.org/assignments/named-information/named-information.xhtml#hash-alg] established as part of [RFC 6920](#). For example, a value of **1** would match the **sha-256** identifier, which maps to the SHA-256 digest algorithm per Section 6.2 of [FIPS 180-4](#).

The digest algorithm chosen SHALL have a minimum digest length of 256 bits, such as **sha-256** (ID 1 in the registry).

To increase interoperability, DataDigestType, if present, SHALL be within the list of [1, 7, 8, 10, 11, 12].

11.23.9.12. RevocationType

This field SHALL identify the type of file found at the DataUrl for this entry. Values supported are:

- 0: Undefined. This value SHALL NOT appear
- 1: [RFC 5280](#) Certificate Revocation List (CRL)
- Other: reserved for future use.

11.23.9.13. SchemaVersion

The SchemaVersion field value history for this schema is provided below:

Version	Description
0	Initial Release

11.23.10. APIs / CLI

The Ledger comes with a set of secure APIs and CLI. More details available [here](https://github.com/zigbee-alliance/distributed-compliance-ledger/blob/master/docs/transactions.md) [https://github.com/zigbee-alliance/distributed-compliance-ledger/blob/master/docs/transactions.md].

11.24. Joint Fabric Datastore Cluster

The Joint Fabric Datastore Cluster is a cluster that provides a mechanism for the [Joint Fabric](#) Administrators to manage the set of Nodes, Groups, and Group membership among Nodes in the [Joint Fabric](#).

When an Ecosystem Administrator Node is commissioned onto the [Joint Fabric](#), the Ecosystem Administrator Node has no knowledge of what Nodes and Groups are present, or what set-up information related to the [Joint Fabric](#) is provided by the user. To address lack of knowledge, the Joint Fabric Datastore provides the information required for all Ecosystem Administrators to maintain a consistent view of the [Joint Fabric](#) including Nodes, Groups, settings and privileges.

The Joint Fabric Datastore contains the access control configuration for the Joint Fabric - the