

Fabric Administrators SHALL use groups in the Datastore for managing access to Nodes. One goal of this approach is to avoid creating ACL entries on Nodes which reference a single NodeID, which does not scale as the number of Controller NodeIDs increases. Instead, ACLs can reference the CAT tag of the group or the GroupID of the group, depending upon the type of access intended. Each group in the Datastore may contain a CAT tag for use in unicast access to group members, and may contain a KeySet for use in broadcast access to group members.

In order to add a new access privilege to NodeA by ControllerB, the **Joint Fabric** Administrator SHALL identify a group to use for this grant (using [Section 11.24.7.4, “AddGroup Command”](#) to create a new one if needed), and call [Section 11.24.7.15, “AddGroupIDToEndpointForNode Command”](#) and [Section 11.24.7.19, “AddACLToNode Command”](#) in order to configure NodeA to allow access by the group. Next, the Administrator SHALL provide a NOC to the controller containing the CAT tag specified for the given group.

In order to remove an access privilege grant for ControllerB on NodeA, the **Joint Fabric** Administrator SHALL revoke access to the group by ControllerB (see [Section 11.24.4.5, “Removing a Node from a Group”](#)) and in doing so, ensure that the CAT version for the Group Information Entry is incremented.

11.24.5. Data Types

11.24.5.1. DatastoreStateEnum Type

This data type is derived from [enum8](#).

Value	Name	Summary	Conformance
0	Pending	Target device operation is pending	M
1	Committed	Target device operation has been committed	M
2	DeletePending	Target device delete operation is pending	M
3	CommitFailed	Target device operation has failed	M

11.24.5.2. DatastoreStatusEntryStruct Type

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	State	DatastoreStateEnum			Pending	R V	M
1	Update-Time-stamp	epoch-s	all			R V	M