

FriendlyName Field

The friendly name for the group.

GroupKeySetID Field

The unique identifier for the group key set.

This value MAY be null when multicast communication is not used for the group. When GroupPermission is Admin or Manage, this value SHALL be null.

A value of 0 is not allowed since this value is reserved for IPK and the group entry for this value is not managed by the Datastore.

GroupCAT Field

CAT value for this group. This is used for control of individual members of a group (non-broadcast commands).

Allowable values include the range 0x0000 to 0xEFFF, and the [Administrator CAT](#) and [Anchor CAT](#) values.

This value MAY be null when unicast communication is not used for the group.

GroupCATVersion Field

Current version number for this CAT.

This value SHALL be null when GroupCAT value is null.

GroupPermission Field

The permission level associated with ACL entries for this group. There should be only one Administrator group per fabric, and at most one Manage group per Ecosystem (Vendor Entry).

11.24.5.6. DatastoreBindingTargetStruct Type

The DatastoreBindingTargetStruct represents a Binding on a specific Node (identified by the DatastoreEndpointBindingEntryStruct) which is managed by the Datastore. Only bindings on a specific Node that are fabric-scoped to the Joint Fabric are managed by the Datastore. As a result, references to nodes and groups are specific to the Joint Fabric.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
1	Node	node-id	all				Endpoint
2	Group	group-id	min 1				!Endpoint
3	Endpoint	endpoint-no	all				!Group
4	Cluster	cluster-id	all				0