

ID	Name	Direction	Response	Access	Conformance
0x12	AddACLToNode	Client ⇒ Server	Y	A	P, M
0x13	RemoveACLFromNode	Client ⇒ Server	Y	A	P, M

11.24.7.1. AddKeySet Command

This command SHALL be used to add a KeySet to the [Joint Fabric](#) Datastore Cluster of the accessing fabric.

The data for this command is as follows:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupKey-Set	Datastore-GroupKey-SetStruct				M

GroupKeySet represents the KeySet to be added to the [Joint Fabric](#) Datastore Cluster.

Upon receipt of this command, the Datastore SHALL:

1. Ensure there are no KeySets in the KeySetList attribute with the given GroupKeySetID.
2. If a match is found, return CONSTRAINT_ERROR.
3. Add the [Epoch Key Entry](#) for the KeySet to the KeySetList attribute.

11.24.7.2. UpdateKeySet Command

This command SHALL be used to update a KeySet in the [Joint Fabric](#) Datastore Cluster of the accessing fabric.

The data for this command is as follows:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupKey-Set	Datastore-GroupKey-SetStruct				M

GroupKeySet represents the KeySet to be updated in the [Joint Fabric](#) Datastore Cluster.

Upon receipt of this command, the Datastore SHALL:

1. Find the Epoch Key Entry for the KeySet in the KeySetList attribute with the given GroupKeySetID, and update any changed fields.
2. If entry is not found, return NOT_FOUND.