

3. If any fields are changed as a result of this command:
 - a. Iterate through each Node Information Entry:
 - i. If the NodeKeySetList contains an entry with the given GroupKeySetID:
 - A. Update the Status on the given [DatastoreNodeKeySetEntryStruct](#) to **Pending**.
 - B. Update the GroupKeySet on the given Node with the new values.
 - I. If successful, update the Status on this [DatastoreNodeKeySetEntryStruct](#) to **Committed**.
 - II. If not successful, update the State field of the StatusEntry on this [DatastoreNodeKeySetEntryStruct](#) to **CommitFailed** and FailureCode code to the returned error. The pending change SHALL be applied in a subsequent [Node Refresh](#).

11.24.7.3. RemoveKeySet Command

This command SHALL be used to remove a KeySet from the [Joint Fabric](#) Datastore Cluster of the accessing fabric.

The data for this command is as follows:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupKey-SetID	uint16	all			M

GroupKeySetID represents the unique identifier for the KeySet to be removed from the [Joint Fabric](#) Datastore Cluster.

Attempt to remove the [IPK](#), which has GroupKeySetID of 0, SHALL fail with response CONSTRAINT_ERROR.

Upon receipt of this command, the Datastore SHALL:

1. If entry is not found, return NOT_FOUND.
2. Ensure there are no Nodes using this KeySet. To do this:
 - a. Iterate through each Node Information Entry:
 - i. If the NodeKeySetList list contains an entry with the given GroupKeySetID, and the entry does NOT have Status **DeletePending**, then return CONSTRAINT_ERROR.
3. Remove the [DatastoreGroupKeySetStruct](#) for the given GroupKeySetID from the GroupKeySetList attribute.

11.24.7.4. AddGroup Command

This command SHALL be used to add a group to the [Joint Fabric](#) Datastore Cluster of the accessing fabric.

The data for this command is as follows: