

ACLList Entry in the Datastore.

- iii. If the FriendlyName changed:
 - A. Iterate through each Endpoint Information Entry:
 - I. If the GroupIDList contains an entry with the given GroupID:
 - 1. Update the GroupIDList Entry in the Datastore with the new values and Status **Pending**
 - 2. Update the Groups on the given Node with the new values.
 - 1. If the update succeeds, set the Status to **Committed** on the GroupIDList Entry in the Datastore.
 - 2. If not successful, the pending change SHALL be applied in a subsequent **Node Refresh**.

11.24.7.6. RemoveGroup Command

This command SHALL be used to remove a group from the **Joint Fabric** Datastore Cluster of the accessing fabric.

The data for this command is as follows:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupID	group-id	all			M

GroupID represents the unique identifier for the group to be removed from the **Joint Fabric** Datastore Cluster.

Attempts to remove a group with GroupCAT value set to **Administrator CAT** or **Anchor CAT** SHALL fail with CONSTRAINT_ERROR.

Upon receipt of this command, the Datastore SHALL:

- 1. If entry is not found, return NOT_FOUND.
- 2. Ensure there are no Nodes in this group. To do this:
 - a. Iterate through each Node Information Entry:
 - i. If the GroupIDList contains an entry with the given GroupID, and the entry does NOT have Status **DeletePending**, then return CONSTRAINT_ERROR.
- 3. Remove the **DatastoreGroupInformationEntryStruct** for the Group with the given GroupID from the GroupList attribute.

11.24.7.7. AddAdmin Command

This command SHALL be used to add an admin to the **Joint Fabric** Datastore Cluster of the accessing fabric.

The data for this command is as follows: