

The data for this command is as follows:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	NodeID	node-id	all			M
1	EndpointID	endpoint-no	all			M
2	GroupID	group-id	all			M

GroupID represents the unique identifier for the group to be removed from the endpoint.

EndpointID represents the unique identifier for the endpoint to be updated in the [Joint Fabric](#) Datastore Cluster.

NodeID represents the unique identifier for the node to which the endpoint belongs.

Upon receipt of this command, the Datastore SHALL:

1. Confirm that an Endpoint Information Entry exists for the given NodeID and EndpointID, and if not, return NOT_FOUND.
2. Ensure the Group List for the Endpoint Information Entry with the given NodeID and EndpointID does not include an entry for the given Group. If it does:
 - a. Update the status to **DeletePending** of the Group entry for the given Group ID in the Group List.
 - b. Remove this Group entry for the given Endpoint ID on the given Node ID.
 - i. If this succeeds, remove the Group entry for the given Group ID in the Group List for this NodeID and EndpointID in the Datastore.
 - ii. If not successful, the pending change SHALL be applied in a subsequent [Node Refresh](#).
3. Ensure the Group Key List for the Node Information Entry with the given NodeID does not include the KeySet for the given Group ID. If it does:
 - a. Update the status to **DeletePending** for the entry for the KeySet of the given Group ID in the Node Group Key List.
 - b. Remove the Group Key Entry for this KeySet from the given Node ID.
 - i. If this succeeds, remove the KeySet entry for the given Node ID.
 - ii. If not successful, update the Status to **CommitFailed** and the FailureCode to the returned error. The error SHALL be handled in a subsequent [Node Refresh](#).

11.24.7.17. AddBindingToEndpointForNode Command

This command SHALL be used to add a binding to an endpoint for a node in the [Joint Fabric](#) Datastore Cluster of the accessing fabric.

The data for this command is as follows: