

store Cluster.

NodeID represents the unique identifier for the node to which the endpoint belongs.

Upon receipt of this command, the Datastore SHALL:

- 1. Confirm that an Endpoint Information Entry exists for the given NodeID and EndpointID, and if not, return NOT_FOUND.
- 2. Ensure the Binding List for the Node Information Entry with the given NodeID does not include an entry with the given ListID. If it does:
 - a. Update the status to DeletePending for the given Binding in the Binding List.
 - b. Remove this Binding from the given Node ID.
 - i. If this succeeds, remove the given Binding from the Binding List.
 - ii. If not successful, update the Status to CommitFailed and the FailureCode to the returned error. The error SHALL be handled in a subsequent Node Refresh.

11.24.7.19. AddACLToNode Command

This command SHALL be used to add an ACL to a node in the Joint Fabric Datastore Cluster of the accessing fabric.

The data for this command is as follows:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	NodeID	node-id	all			M
1	ACLEntry	DatastoreAccessControlEntryStruct				M

NodeID represents the unique identifier for the node to which the ACL is to be added.

ACLEntry represents the ACL to be added to the Joint Fabric Datastore Cluster.

Upon receipt of this command, the Datastore SHALL:

- 1. Confirm that a Node Information Entry exists for the given NodeID, and if not, return NOT_FOUND.
- 2. Ensure the ACL List for the given NodeID includes the given ACLEntry. If it does not:
 - a. Add the ACLEntry to the ACL List for the given NodeID. The new entry’s status SHALL be set to Pending.
 - b. Add this ACLEntry to the given Node ID.
 - i. If this succeeds, update the new ACLEntry in the Datastore to Committed.
 - ii. If not successful, update the Status to CommitFailed and the FailureCode to the returned error. The error SHALL be handled in a subsequent Node Refresh.