

with a **NOC** containing the Anchor CAT. All Administrator devices participating in [Section 12.2, “Joint Fabric”](#) SHALL contain an ACL entry granting **Administer** privilege with the **CaseSubjectAdmin** set to the Anchor CAT. During commissioning of any Administrator Node onto the [Section 12.2, “Joint Fabric”](#) the **CaseAdminSubject** field SHALL be set to the Anchor CAT upon invoking the **AddNOC** command. Any Node advertising as a [Section 12.2, “Joint Fabric”](#) Anchor or Datastore SHALL contain the Anchor CAT in its NOC. A NOC containing the Anchor CAT SHALL be issued only by the [Section 12.2, “Joint Fabric”](#) Anchor ICAC.

Any client that discovers an Anchor Node with DNS-SD and connects to the Node via CASE SHALL check if the Anchor CAT is present in the NOC using the **Peer CASE Authenticated Tags** and that the NOC chains up to the [Anchor ICAC](#) before taking any [Section 12.2, “Joint Fabric”](#) actions on the Node. This SHALL be required in order to verify that the Node is authorized to act as an Anchor of the [Section 12.2, “Joint Fabric”](#).

If the Anchor CAT is already in use in a fabric that wants to participate in the [Section 12.2, “Joint Fabric”](#) then its Administrator first needs to take the required steps for updating it with a non-overlapping Anchor CAT. This may involve updating ACLs and **NOCs** on the Nodes wishing to participate in the [Section 12.2, “Joint Fabric”](#).

12.2.5. Joint Commissioning Method (JCM)

NOTE Support for Joint Commissioning Method is provisional.

This method SHALL be implemented for Commissioners and Administrators that support Joint Fabric.

Given a pre-existing Matter fabric, Fabric A, managed by Ecosystem A with its own administrator and commissioner nodes, a Joint Fabric can be created with another Ecosystem B. This allows all devices of Ecosystem A and Ecosystem B to communicate using a single operational root of trust. Either ecosystem can add devices to the new joint fabric. Joint Commissioning Management (JCM) is the process through which an administrator of Ecosystem B receives a **cross-signed ICAC** from the Anchor Administrator of Ecosystem A. While Ecosystem A MAY contain multiple administrator nodes, only the Anchor Administrator SHALL be able to execute JCM.

The joint operation ensures that ICA's from both Fabric A and Fabric B are signed by the Anchor CA (the Root CA of the fabric selected to become the Anchor Fabric), establishing a common trust between all devices of the original Fabric A and Fabric B and all newly added devices to the “Joint Fabric”.

The Joint Fabric contains multiple ecosystems whose ICACs are cross-signed by the Anchor CA. Therefore, all ecosystems participating in the [Section 12.2, “Joint Fabric”](#) SHALL use an **ICAC** to sign **NOCs**. Signing NOCs with a Root CA different than the Anchor CA is not permitted in the Joint Fabric.

In the figure below, Ecosystem A with Fabric A acts as the Anchor Fabric and Ecosystem B with Fabric B as joining fabric to create a Joint Fabric between the two Ecosystems. Here are the JCM steps:

1. Ecosystem B Administrator SHALL become commissionable for JCM. This SHALL happen using one of the two methods below: