

vided in this notification and the User MAY have the option of leaving the Joint Fabric (e.g.: User doesn't want to join Ecosystem B with A's Vendor ID).

Ecosystem B Administrator MAY now use the below commands from [Operational Credentials cluster](#) to update each Node in the Fabric B to join Fabric A:

1. Update [Section 11.18.5.5, "TrustedRootCertificates"](#) by using [Section 11.18.6.13, "AddTrusted-RootCertificate"](#) with the [RootCACertificate](#) parameter set to the RCAC of Fabric A
2. Update Node Operational Credentials using [AddNOC](#):
 - a. [NOCValue](#) SHALL contain a NOC issued by the [JFCrossSignedICAC](#). Subject DN of the [NOCValue](#) SHALL encode a [matter-fabric-id](#) attribute whose value SHALL be identical with the value of the [matter-fabric-id](#) attribute from [JFCrossSignedICAC](#)
 - b. [ICACValue](#) parameter SHALL be set to the value of [JFCrossSignedICAC](#)
 - c. [IPKValue](#) parameter SHALL be set to the value of the IPK found in the [GroupKeySetList](#) hold by the Joint Fabric Datastore of Fabric A
 - d. [CaseAdminSubject](#) SHALL contain an Administrator CAT whose version is indicated by the corresponding entry from [GroupList](#) attribute hold by the Joint Fabric Datastore of Fabric B.
 - e. [AdminVendorId](#) field SHALL be set to the value of the AdminVendorIdValue found in the local Fabric Table under the [AdministratorFabricIndex](#).
3. Remove the old Trusted Root CA Certificate and the associated Fabric B using the [Section 11.18.6.12, "RemoveFabric"](#) command

User Consent MAY be needed each time a new Node/subset of Nodes is shared from Fabric B to Fabric A. While moving Nodes from Fabric B to Fabric A, Ecosystem B SHALL invoke the required commands on the Joint Fabric Datastore cluster owned by the Anchor Administrator of Fabric B in order to remove those Nodes and on the Joint Fabric Datastore cluster owned by Ecosystem A Anchor Administrator in order to add those Nodes.