

- b. obtain user consent prior to sending the [TransferAnchorRequest](#) command.
2. Administrator A SHALL:
 - a. check that the NOC used by Administrator B during the CASE session contains an Administrator CAT.
 - b. check that user provided consent that allows the transfer of the Anchor role to a different Administrator. If not, then [TransferAnchorResponse](#) command with StatusCode set to [TransferAnchorStatusNoUserConsent](#) SHALL be sent and the procedure stopped here.
 - c. check all the [Datastore](#) entries of type [DatastoreStatusEntryStruct](#). If any of these entries has a value that equals to [Pending](#) or to [DeletePending](#) then [TransferAnchorResponse](#) command with StatusCode set to [TransferAnchorStatusDatastoreBusy](#) SHALL be sent and the procedure stopped here.
 - d. put Joint Fabric Datastore in read only state by setting the Datastore [StatusEntry](#) to [DeletePending](#).
 - e. stop DNS-SD advertising of the [Administrator](#), [Anchor](#) and [Datastore](#) capability inside the [JF TXT key](#).
3. All other Joint Fabric Administrators SHALL:
 - a. stop commissioning of any new devices into the Joint Fabric once it detects that Datastore [StatusEntry](#) equals [DeletePending](#).
4. Administrator B SHALL:
 - a. copy (through attribute read, BDX) Joint Fabric Datastore from Administrator A.
 - b. set the Datastore [StatusEntry](#) to [Committed](#).
 - c. set the value of the Datastore [AnchorNodeId](#) attribute to the value of its Node ID.
 - d. increase [Section 12.2.4.1, "Administrator CAT"](#) version.
 - e. use following commands from [Operational Credentials cluster](#) on the other Joint Fabric Administrators:
 - i. update [Section 11.18.5.5, "TrustedRootCertificates"](#) by using [Section 11.18.6.13, "AddTrustedRootCertificate"](#).
 - ii. update Node Operational Credentials using [AddNOC](#). [NOCs](#) SHALL contain an updated version of the Administrator CAT.
 - f. issue itself a new NOC with the updated version of the Anchor CAT.
 - g. set itself as the new Datastore provider and Anchor Administrator by advertising the [Administrator](#), [Anchor](#) and [Datastore](#) capabilities inside the [JF TXT key](#).
 - h. send [TransferAnchorComplete](#) to Administrator A to announce that transition to Anchor Administrator is complete.
5. All other Joint Fabric Administrators SHALL:
 - a. subscribe to the new Datastore provider (Administrator B) having discovered the new [Datastore](#) capability via Service Discovery of the [JF TXT key](#).
 - b. check that the [NOC](#) used by the new Datastore provider (Administrator B) during the first CASE session contains an [Section 12.2.4.2, "Anchor CAT"](#) and that the NOC chains up to the