

14.4.4. Data Types

14.4.4.1. TLSCAID Type

This data type is derived from uint16 and represents a provisioned certificate authority certificate with valid values from 0 to 65534. This value SHOULD start at 0 and monotonically increase by 1 with each new allocation provisioned by the Node. A value incremented past 65534 SHOULD wrap to 0. The Node SHALL verify that a new value does not match any other value for this type. If such a match is found, the value SHALL be changed until a unique value is found.

14.4.4.2. TLSCCDID Type

This data type is derived from uint16 and represents a provisioned client certificate with valid values from 0 to 65534. This value SHOULD start at 0 and monotonically increase by 1 with each new allocation provisioned by the Node. A value incremented past 65534 SHOULD wrap to 0. The Node SHALL verify that a new value does not match any other value for this type. If such a match is found, the value SHALL be changed until a unique value is found.

14.4.4.3. TLSCertStruct Type

This encodes the mapping between a [TLSCAID](#) and the associated root certificate.

Access Modifier: Fabric Scoped							
ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	CAID	TLSCAID	0 to 65534				M
1	Certificate	octstr	max 3000				O

CAID Field

This field SHALL be a [TLSCAID](#) representing the unique Certificate Authority ID.

Certificate Field

This field SHALL be an octet string that represents a certificate encoded using DER encoding.

When this field exists and is read over a [Large Message](#) capable transport, it SHALL be included. When this field exists and is read over a non [Large Message](#) capable transport, it SHALL NOT be included. To get the full details of a certificate use the [FindRootCertificate](#) command.

14.4.4.4. TLSClientCertificateDetailStruct Type

This encodes a TLS Client Certificate and corresponding ICAC chain.

Access Modifier: Fabric Scoped							
ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	CCDID	TLSCCDID	0 to 65534				M