

Access Modifier: Fabric Scoped							
1	ClientCertificate	octstr	max 3000	X			O
2	IntermediateCertificates	list[octstr]	max 10 [max 3000]				O

CCDID Field

This field SHALL be a [TLSCCID](#) representing the unique Client Certificate ID.

ClientCertificate Field

This field SHALL be an octet string that represents a TLS Client Certificate encoded using DER encoding.

When this field exists and is read over a [Large Message](#) capable transport, it SHALL be included. When this field exists, is non-NULL, and is read over a non [Large Message](#) capable transport, it SHALL NOT be included. To get the full details of a certificate use the [FindClientCertificate](#) command.

A NULL value indicates that the [TLS Client Certificate Signing Request \(CSR\) Procedure](#) has not yet completed.

IntermediateCertificates Field

This field SHALL be a list of octet strings representing one or more ICACs (also encoded using DER) that form a Certificate Chain up to, but not including, the [TLSRCAC](#).

When this field exists and is read over a [Large Message](#) capable transport, it SHALL be included. When this field exists, is non-empty, and is read over a non [Large Message](#) capable transport, it SHALL NOT be included. To get the full details of a certificate use the [FindClientCertificate](#) command.

An empty value means that no intermediate certificates are needed for the TLS Server to validate the [ClientCertificate](#).

14.4.5. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	Max-RootCertificates	uint8	5 to 254	F		R V	M
0x0001	Provisioned-RootCertificates	list[TLSCertStruct]	max Max-RootCertificates	N		R V S	M