

Effect on Receipt

The following process SHALL be followed when the server receives this command:

- If the [ProvisionedRootCertificates](#) list is empty:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If the passed in *CAID* is null:
 - Create an empty list of [TLSCertStruct](#).
 - For each entry in [ProvisionedRootCertificates](#):
 - If the [associated fabric](#) of the entry matches the [accessing fabric](#):
 - Add a populated [TLSCertStruct](#) entry for the CAID to the resulting list.
 - If the resulting list has no entries:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- Else if the passed in *CAID* is not null:
 - If there is no entry in the [ProvisionedRootCertificates](#) list that has a [CAID Field](#) matching the passed in *CAID*:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
 - If the [associated fabric](#) of the [TLSCertStruct](#) for that entry does not equal the [accessing fabric](#):
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
 - Create a list of one [TLSCertStruct](#) and populate with the values from that entry.
- Return the resulting list in the corresponding [FindRootCertificateResponse](#) command.

14.4.6.4. FindRootCertificateResponse Command

This command SHALL be generated in response to a FindRootCertificate command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	CertificateDetails	list[TLSCertStruct]	1 to Max-RootCertificates			M

CertificateDetails Field

This field SHALL be a list of [TLSCertStructs](#) containing a minimum of one [TLSCertStruct](#).