

CAID Field

This field SHALL be a [TLSCAID](#) representing the unique Certificate Authority ID.

Effect on Receipt

The following process SHALL be followed when the server receives this command:

- If the [ProvisionedRootCertificates](#) list is empty:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If there is no entry in the [ProvisionedRootCertificates](#) list that has a [CAID Field](#) matching the passed in *CAID*:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If the [associated fabric](#) of the [TLSCertStruct](#) for that entry does not equal the [accessing fabric](#):
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If the passed in *CAID* equals the [CAID](#) of any entry in the [ProvisionedEndpoints](#) list in the [TLS Client Management Cluster](#):
 - Fail the command with the status code INVALID_IN_STATE, and end processing with no other side effects.
- Remove the entry for the passed in *CAID* from the [ProvisionedRootCertificates](#) list.

14.4.6.8. ClientCSR Command

This command SHALL be generated to request the Node generates a certificate signing request for a new TLS key pair or use an existing CCDID for certificate rotation.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Nonce	octstr	32			M
1	CCDID	TLSCCDID	0 to 65534	X		M

Nonce Field

This field SHALL be an octet string that represents the nonce to be signed by the private key used in the CSR, with the resulting signature returned in the [NonceSignature](#) field of [ClientCSRResponse](#).

CCDID Field

This field SHALL be a [TLSCCDID](#) representing the unique Client Certificate Details ID. If NULL, a new key pair and CCDID will be generated. If non-NULL, the existing key-pair for the CCDID will be used.