

Effect on Receipt

The following process SHALL be followed when the server receives this command:

- If the passed in *CCDID* is NULL:
 - If the count of entries in the [ProvisionedClientCertificates](#) list where the [associated fabric](#) matches the [accessing fabric](#), is equal to the [MaxClientCertificates](#) value:
 - Fail the command with the status code `RESOURCE_EXHAUSTED`, and end processing with no other side effects.
 - Generate a new key pair using [Crypto_GenerateKeypair](#).
 - If a key collision is detected against any other TLS key pair or Operational credential key pair:
 - Discard the new key pair.
 - Fail the command with the status code `DYNAMIC_CONSTRAINT_ERROR`, and end processing with no other side effects.
 - Generate a new [TLSCCDID](#) value.
 - Create a new [TLSClientCertificateDetailStruct](#) associated with the [accessing fabric](#).
 - Set the [CCDID](#) field with the newly created [TLSCCDID](#) value, and associate the key pair with it.
 - Set the [ClientCertificate](#) and [IntermediateCertificates](#) fields to NULL.
 - Add the [TLSClientCertificateDetailStruct](#) to the [ProvisionedClientCertificates](#) list.
- Else if the passed in *CCDID* is not NULL:
 - If there is no entry in the [ProvisionedClientCertificates](#) list that has a matching [CCDID](#) to the passed in *CCDID*:
 - Fail the command with the status code `NOT_FOUND`, and end processing with no other side effects.
 - If the [associated fabric](#) of that entry does not equal the [accessing fabric](#):
 - Fail the command with the status code `NOT_FOUND`, and end processing with no other side effects.
- Generate a `tls_csr` using the TLS key pair by following the format and procedure in [PKCS #10](#), which includes a signature using the private key (see [RFC 2986](#) section 4.2) associated with the public key which is the `subjectPublicKey` field of the CSR. The CSR subject MAY be any value and the device SHOULD NOT expect the final certificate to contain any of the CSR subject DN attributes.
- Compute an [ec-signature](#) using [Crypto_Sign\(\)](#) of the passed in *Nonce*, and encode the result as an octet string into `tls_nonce_signature`.

```
tls_nonce_signature = Crypto_Sign(  
    message = Nonce,  
    privateKey = TLS Private Key
```