

Note: When using this command for client certificate rotation, only new underlying TLS connections (established after this finishes processing), will use the updated Certificate.

14.4.6.11. FindClientCertificate Command

This command SHALL return the [TLSClientCertificateDetailStruct](#) for the passed in CCDID, or all TLS client certificates for the [accessing fabric](#), based on the contents of the CCDID field.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	CCDID	TLSCCDID	all	X		M

CCDID Field

This field SHALL be a [TLSCCDID](#) representing the unique Client Certificate Details ID.

Effect on Receipt

The following process SHALL be followed when the server receives this command:

- If the [ProvisionedClientCertificates](#) list is empty:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If the passed in *CCDID* is null:
 - Create a list of [TLSClientCertificateDetailStruct](#)
 - For each entry in [ProvisionedClientCertificates](#):
 - If the entry's [associated fabric](#) matches the [accessing fabric](#):
 - Add a populated [TLSClientCertificateDetailStruct](#) entry for the passed in *CCDID* to the resulting list.
 - If the resulting list has no entries:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- Else if the passed in *CCDID* is not null:
 - If there is no entry in the [ProvisionedClientCertificates](#) list that has a [CCDID](#) matching the passed in *CCDID*:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
 - If the [associated fabric](#) of that entry does not equal the [accessing fabric](#):
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
 - Create a list of one [TLSClientCertificateDetailStruct](#) and populate with the values from that entry for the requested *CCDID*.
- Return the list as the [CertificateDetails](#) field, in the corresponding [FindClientCertificateResponse](#)