

[ClientCertificateResponse](#) command.

14.4.6.14. LookupClientCertificateResponse Command

This command SHALL be generated in response to a LookupClientCertificate command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	CCDID	TLSCCDID	0 to 65534			M

CCDID Field

This field SHALL be a [TLSCCDID](#) representing the unique Client Certificate Details ID.

14.4.6.15. RemoveClientCertificate Command

This command SHALL be used to request the Node removes all stored information for the provided CCDID.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	CCDID	TLSCCDID	0 to 65534			M

CCDID Field

This field SHALL be a [TLSCCDID](#) representing the unique Client Certificate Details ID.

Effect on Receipt

The following process SHALL be followed when the server receives this command:

- If the [ProvisionedClientCertificates](#) list is empty:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If there is no entry in the [ProvisionedClientCertificates](#) list that has a [CCDID](#) matching the passed in *CCDID*:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If the [associated fabric](#) of that entry does not equal the [accessing fabric](#):
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If the passed in *CCDID* equals the [CCDID](#) of any entry in the [ProvisionedEndpoints](#) list in the [TLS Client Management Cluster](#):
 - Fail the command with the status code INVALID_IN_STATE, and end processing with no other side effects.
- Remove the entry for the passed in *CCDID* from the [ProvisionedClientCertificates](#) list.